













Axis video encoders

	1-channel video encoders					4- and 6-channel video encoders			
	AXIS 241S 	AXIS 243SA 	AXIS 247S 	AXIS Q7401 ¹ 	AXIS 240Q 	AXIS 241Q 	AXIS 241QA 	AXIS 243Q 	AXIS Q7406 
Video compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG	Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	Motion JPEG, H.264
Max video resolution (pixels)	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	D1: 720x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	D1: 720x480
Frames per second H.264 in maximum resolution				30 (D1)					30 (D1)
Frames per second MPEG-4 in maximum resolution	21 (4CIF), 30 (2CIF)	30 (4CIF)	27 (4CIF), 30 (VGA)			21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels	21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels	30 (4CIF) per channel	
Frames per second Motion JPEG in maximum resolution	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (D1)	6 (4CIF) per channel	30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels	30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels	30 (4CIF) per channel	30 (4CIF) per channel
Video source	1 BNC composite or Y/C video input ²	1 BNC composite or Y/C video input ²	1 BNC composite input	1 BNC composite input	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	6 BNC composite inputs
Audio support		Two-way	One-way	Two-way			Two-way		
Alarm in-/outputs	4/4	4/4	1/1	4 configurable inputs/outputs	4/4	4/4	4/4	4/4	2 configurable inputs/ outputs per channel
Intelligent video	Motion detection	Motion detection, Audio detection, Active tampering alarm	Motion detection, Audio detection	Motion detection, Audio detection, Active tampering alarm	Motion detection	Motion detection	Motion detection	Motion detection, Active tampering alarm	Motion detection, Active tampering alarm
Pan/tilt/zoom support	● ³	● ³		● ³	● ³	● ³	● ³	● ³	● ³
Security	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)			Class 2/3 ⁴	Class 2/3 ⁴					
Serial connectors	RS-232, RS-485	RS-232, RS-485		RS-422/485	RS-232, RS-485	RS-232, RS-485	RS-232, RS-485	RS-485	RS-485
Standalone version	●	●	●	●	●	●	●		
Blade version	●				●	●		●	●
Axis part #	0186-004	0256-004	0272-001	0288-004	0232-004	0185-004	0230-004	0261-001	0289-001





1) Supports local storage with SD/SDHC card 2) Y/C video requires converter cable 3) Requires additional third-party pan/tilt/zoom device 4) Includes power output for analog camera

Rack solutions

Designed for high-density installations, Axis video encoder rack solutions accommodate multiple video encoder blades in the same rack.





	AXIS 291 1U Video Server Rack	AXIS Video Server Rack	AXIS Q7900 Rack
			
Number of slots	3	12	14
Blades supported	AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q	AXIS 240Q AXIS 241Q AXIS 241S	AXIS Q7406 AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q
Maximum number of channels	18	48	84
Rack size	1U	3U	4U
Rack height	19"	19"	19"
Built-in power supply	●	●	● Redundant Power Supply
Network	Ethernet 10BaseT/ 100BaseTX/1000BaseT (1 Gigabit Ethernet Port)	10BaseT/100BaseTX	Ethernet 10BaseT/ 100BaseTX/1000BaseT (4 Gigabit Ethernet Ports)
Axis part #	0267-004	0192-004	0287-004
Axis Video Server/Encoder Blades			
AXIS 241S Blade AXIS 240Q Blade AXIS 241Q Blade AXIS 243Q Blade AXIS Q7406 Blade		Axis part # 0210-011 Axis part # 0232-024 Axis part # 0209-011 Axis part # 0261-001 Axis part # 0289-001	

Accessories

AXIS 295 Video Surveillance Joystick	
AXIS 295 Video Surveillance Joystick is a USB device specifically designed for responsive and accurate control of all Axis pan/tilt/zoom and dome network cameras. It features a three-axis, durable (Hall-effect) joystick and twelve programmable push-buttons. Easy to install, just connect the joystick to the USB port and control the Axis cameras. 	
Axis part # 0248-001	
IR-LED Illuminators	
Illuminators for indoor/outdoor surveillance in low light or complete darkness. Use with Axis day & night cameras: 	
AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 221, AXIS 223M, AXIS 225FD, AXIS 232D+ and AXIS 233D Network Cameras.	
AXIS T90A01 850nm 50 Deg PoE AXIS T90A20 850nm 120-180 Deg AXIS T90A21 850nm 50-100 Deg AXIS T90A33 850nm 10-20 Deg AXIS T90A40 850nm 120-180 Deg	Axis part # 5013-011 Axis part # 5013-201 Axis part # 5013-211 Axis part # 5013-331 Axis part # 5013-401
Power-over-Ethernet Midspans and Splitters	
Axis Power over Ethernet midspan and splitters offer an easy, fast and cost-effective solution for powering network video products without the need to install power outlets and electrical cabling. 	
High PoE midspans and splitters are available for network cameras such as PTZ and PTZ dome cameras that require higher power consumption.	
Power-over-Ethernet Midspans	
1-port (high PoE) 1-port 8-port 16-port	Axis part # 5014-004 Axis part # 0226-004 Axis part # 5012-004 Axis part # 5012-014
Power-over-Ethernet Active Splitters	
	Axis part # 5014-501 (high PoE 12V) Axis part # 5014-511 (high PoE 24V) Axis part # 0170-004-01 ¹ Axis part # 0227-001 Axis part # 5008-001 (5V)
AXIS 292 Network Video Decoder	
AXIS 292 Network Video Decoder decodes digital video and audio streams into analog video signals. 	
Axis part # 0213-004	












1) Not 802.3af compliant

Video management software

AXIS Camera Station	
Comprehensive, easy-to-use video management software for monitoring, recording, playback and event management. Specially designed for Axis network cameras and video encoders. 	
10-camera base license 4-camera base license 20-camera add on license 5-camera add on license 1-camera add on license 1-year software upgrade	Axis part # 0202-004 Axis part # 0202-054 Axis part # 0202-264 Axis part # 0202-014 Axis part # 0202-034 Axis part # 0202-024
AXIS Camera Station One	
Software solution for viewing and recording live video from a single Axis network camera. Available for free download. 	
For more information, visit www.axis.com/products/video/software/	
AXIS Camera Management	
Powerful and efficient installation and management tool for Axis network video products. Available for free download. 	
Axis' Application Development Partners	
A wide variety of software solutions for video surveillance, remote monitoring or broadcasting are available from more than 500 Axis Application Development Partners. 	









Distributed by:

Axis fixed dome network cameras

	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor / Outdoor
	AXIS 209FD	AXIS 209FD-R	AXIS 209MFD	AXIS 209MFD-R	AXIS 216FD	AXIS 216FD-V	AXIS 216MFD	AXIS 216MFD-V	AXIS P3301	AXIS P3301-V	AXIS 225FD
											
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CCD
Lens	3.0 mm/F2.0 fixed iris	3.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	3.6 mm/F1.8 fixed iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 5.8 mm/F1.4 DC-iris ¹
Day and night											Automatic
Min illumination/ light sensitivity (lux)	1.5 - 10,000	1.5 - 10,000	3 - 10,000	3 - 10,000	1	1	2	2	1	1	1 (color) 0.2 (B/W)
Compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	1280 x 1024	1280 x 1024	640 x 480	640 x 480	1280 x 1024	1280 x 1024	640 x 480	640 x 480	640 x 480
Frames per second	30 (640x480)	30 (640x480)	12 (1280x1024)	12 (1280x1024)	30 (640x480)	30 (640x480)	12 (1280x1024) 30 (800x600)	12 (1280x1024) 30 (800x600)	30 (640 x 480)	30 (640 x 480)	30 (640x480)
Audio support					Two-way	Two-way	Two-way	Two-way	Two-way	Two-way	
Alarm in-/outputs					1/1	1/1	1/1	1/1	1/1	1/1	2/1
Intelligent video	Motion detection	Motion detection Active tampering alarm	Motion detection	Motion detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Active tampering alarm
Security	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 2	Class 2	Class 2 (without heater)
Serial connectors											RS-485
Outdoor use											●
Other	Tamper-resistant	IP66-rated, rugged, for mobile video surveillance	Tamper-resistant	IP66-rated, rugged, for mobile video surveillance	Tamper-resistant	Vandal-resistant	Tamper-resistant	Vandal-resistant	WDR, Tamper-resistant	WDR, Vandal-resistant	Vandal-resistant, IP66-rated, heater and fan
Axis part #	0281-004	0275-004	0283-004	0286-004	0240-004	0268-004	0278-004	0279-004	0290-004	0292-004	0243-004





1) Also available with varifocal 9-22mm/F1.5 DC-iris Axis part #0243-064, \$999





Axis fixed network cameras

	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor / Outdoor	Indoor / Outdoor
	AXIS 206	AXIS 207	AXIS 207W	AXIS 207MW	AXIS 210	AXIS 210A	AXIS 211¹	AXIS 211A¹
								
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CCD	1/4" progressive scan CCD	1/4" progressive scan CCD	1/4" progressive scan CCD
Lens	4.0 mm/F2.0 fixed iris	4.0 mm/F2.0 fixed iris	4.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	4.0 mm/F1.2 fixed iris CS mount	4.0 mm/F1.2 fixed iris CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount
Day and night								
Min illumination/ light sensitivity (lux)	4 - 10,000	1 - 10,000	1 - 10,000	2 - 10,000	1 - 10,000	1 - 10,000	0.75	0.75
Video compression	Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	640 x 480	1280 x 1024	640 x 480	640 x 480	640 x 480	640 x 480
Frames per second	30 (640x480)	30 (640x480)	30 (640x480)	12 (1280 x 1024)	30 (640x480)	30 (640x480)	30 (640x480)	30 (640x480)
Audio support		One-way	One-way	One-way		Two-way		Two-way
Alarm in-/outputs		1/1	1/1	1/1	1/1	1/1	1/1	1/1
Intelligent video		Motion detection Audio detection	Motion detection Audio detection	Motion detection Audio detection	Motion detection	Motion detection Audio detection	Motion detection	Motion detection Audio detection
Security	Multi-level passwords	Multi-level passwords	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4	IPv4	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	PoE splitter available #5008-001	PoE splitter available #5008-001			PoE splitter available #0227-001	Class 2	Class 2	Class 2
Serial connectors								
Outdoor use							Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing
Other			Wireless 802.11g/b	Wireless 802.11g/b	Changeable lens	Changeable lens	Changeable lens	Changeable lens
Axis part #	0199-004	0235-004	0241-004	0264-004	0197-004	0233-004	0198-004	0223-004





1) Outdoor use requires weather-proof housing 2) Instant one-click pan/tilt/zoom with no moving parts 3) Requires the AXIS 213 Connection Module Axis part #22581, \$99.

Axis pan/tilt/zoom network

Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor
AXIS 211W¹	AXIS 211M¹	AXIS 221¹	AXIS 223M¹
			
1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CCD	1/2.7" progressive scan CCD 2 megapixel
Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 4.0 - 8.0 mm/F1.4 DC-iris, C mount ¹
		Automatic	Automatic
0.75	1	0.65 (color) 0.08 (B/W)	1.5 (color) 0.2 (B/W)
MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
640 x 480	1280 x 1024	640 x 480	1600x900 1600x1200
30 (640x480)	12 (1280x1024) 30 (800x600)	45 (640x480) 60 (480x360)	12 (1600x900) 9 (1600x1200)
Two-way	Two-way		Two-way
1/1	1/1	2/1	2/1
Motion detection Audio detection	Motion detection Audio detection	Motion detection Active tampering alarm	Motion detection Audio detection Active tampering alarm
Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Class 2	Class 2	Class 2	Class 2
		RS-232, RS-485	RS-232, RS-485
Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing
Wireless 802.11g/b, changeable lens	Changeable lens	Changeable lens	Changeable lens
0270-004	0269-004	0221-004	0247-004

	Indoor	Indoor	Indoor / Outdoor	Indoor / Outdoor
	AXIS 212 PTZ²	AXIS 212 PTZ-V²	AXIS 213 PTZ¹	AXIS 214 PTZ¹
				
Image sensor	1/2" progressive scan CMOS 3 megapixel	1/2" progressive scan CMOS 3 megapixel	1/4" CCD	1/4" ExView HAD CCD
Lens	2.7 mm/F1.8 fixed iris 3x instant zoom	2.7 mm/F1.8 fixed iris 3x instant zoom	3.5 - 91 mm auto iris and auto focus 26x optical zoom 12x digital zoom	4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom
Day and night			Configurable Built-in IR lamp	Automatic
Min illumination/ light sensitivity (lux)	10 lux wide mode 20 lux tele mode	10 lux wide mode 20 lux tele mode	1 (color) 0.1 (B/W)	0.3 (color) 0.005 (B/W)
Video compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	4CIF: 704x480	4CIF: 704x480
Frames per second	30 (640x480) in overview	30 (640x480) in overview	30 (4CIF)	30 (4CIF)
Pan/Tilt/Zoom	20 presets 140° pan 105° tilt Guard tour	20 presets 140° pan 105° tilt Guard tour	20 presets 340° pan 100° tilt	20 presets 340° pan 120° tilt
Audio support	Two-way	Two-way	Two-way with AXIS 213CM	Two-way
Alarm in-/outputs	1/1	1/1	2/3 with AXIS 213CM ³	1/1
Intelligent video	Motion detection Audio detection	Motion detection Audio detection	Motion detection	Motion detection Audio detection
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 1	Class 1	PoE active splitter available #0170-004-01	
Serial connectors			RS-232 with AXIS 213CM ³	
Outdoor use			Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing
Other	Continuous motion 24/7	Continuous motion 24/7 Vandal-resistant	Built-in IR light up to 3 m Analog video with AXIS 213CM ³	
Axis part #	0257-004	0280-004	0220-004	0246-004

cameras

Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor
AXIS 215 PTZ¹	AXIS 231D+¹	AXIS 232D+¹	AXIS 233D
			
1/4" CCD	1/4" ExView HAD CCD	1/4" ExView HAD CCD	1/4" ExView progressive scan HAD CCD
3.8 - 46 mm auto iris and auto focus 12x optical zoom 4x digital zoom	4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom	4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom	3.4 - 119 mm auto iris and auto focus 35x optical zoom 12x digital zoom
Automatic		Automatic	Automatic
1 (color) 0.3 (B/W)	0.3 (color)	0.3 (color) 0.005 (B/W)	0.5 (color) 0.008 (B/W)
MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480
30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)
20 presets 360° pan via auto-flip 180° tilt	50 presets 360° endless pan 90° tilt Guard tour	50 presets 360° endless pan 90° tilt Guard tour	100 presets 360° endless pan 180° tilt Guard tour
Two-way			Two-way
1/1	4/4	4/4	4/4
Motion detection Audio detection	Motion detection	Motion detection	Motion detection Audio detection
Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing
Auto-flip and E-flip	Continuous motion 24/7, WDR	Continuous motion 24/7, WDR	Continuous motion 24/7, E-flip, Image stabilizer, WDR, Auto-tracking
0274-004	0251-001	0253-001	0266-004

Axis network camera housings

Axis network camera housings

	Part #	Product	Compatible with:
	5015-101	AXIS T92A10 Housing Aluminum construction - Indoor/outdoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211M, AXIS 221, AXIS 223M
	5010-001	AXIS T95A00 Dome Housing ¹ Aluminum construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ AXIS 231D+, AXIS 232D+, AXIS 233D
	5010-631	AXIS T95A63 Extension Bracket	Extension Bracket for AXIS T95A00 and T95A10 Dome Housing. Used with AXIS T95A62 Ceiling / Parapet bracket.
	5010-641	AXIS T95A64 Corner Bracket	Requires AXIS T95A61 Wall Bracket.
	5010-671	AXIS T95A67 Pole Bracket	Requires AXIS T95A61 Wall Bracket.
	5010-101	AXIS T95A10 Dome Housing ² Aluminum construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ AXIS 231D+, AXIS 232D+, AXIS 233D
	24886	AXIS Indoor Fixed Wall Housing ³	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
	24887	AXIS Indoor Fixed Corner Housing ³	
	24888	AXIS Indoor Fixed Ceiling Housing ³	
	21899	AXIS Indoor Fixed Housing Aluminum construction - Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
	22870	AXIS Indoor Fixed Camera Dome Steel construction - Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
	21898	AXIS Indoor Recessed Enclosure Steel construction - Indoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
	26549	AXIS 206/207 Ceiling-Mount Housing Steel construction - Indoor	AXIS 206, AXIS 207 (not wireless)
	26550	AXIS 206/207 Vandal-Resistant Housing Aluminum construction - Indoor	AXIS 206, AXIS 207 (not wireless)
	24889	AXIS Outdoor Fixed Housing Aluminum construction - Outdoor	AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
	29892	AXIS Fixed Wireless Housing Aluminum construction - Outdoor	AXIS 211W
	25735	AXIS Pendant Dome Indoor Plastic construction - Indoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
	25733	AXIS Pendant Dome Outdoor Plastic construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
	25734	AXIS Pendant Vandal Dome Aluminum construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+
	25736	Gooseneck Wall Mount	Gooseneck wall mount for the AXIS Pendant Dome
	25738	Parapet Mount	Parapet mount for the AXIS Pendant Dome
	22059	Corner Mount Adapter	Corner mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings
	21896	Pole Mount Adapter	Pole mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings.
	26349	Ceiling Mount 12" Extension	Secures AXIS Pendant Dome housings to hard ceilings
	26350	Ceiling Mount 24" Extension	Secures AXIS Pendant Dome housings to hard ceilings
	5500-381	AXIS 225FD Pendant Kit	Connects AXIS 225FD to 25735, 25738, 26349, 26350, or 1-1/2 NPT pipe

1) Power supply included 2) Need PS-24 3) Steel construction - Indoor
For more information, visit www.axis.com/products/video/accessories